## Flammability Certificate 3752 Hem Stitch

**Designtex** 

3752 Hem Stitch was tested and met the following flammability requirements:

ASTM E 84 Unadhered Class A CA TB 117-2013 UL Listed



Page 1

235

Received:05/03/2016 Completed:05/04/2016 Letter: V BG | P.O.#: Test Report #: 3-13142-0-Product Name: Hem Stitch 3752. Fiber Content: 99% Recycled Polyester, 1% Polyester, 57" wide. 11.5 oz/lyd. No Finish.

Identification No Back.

Tested For: Teesha Prezeau

Designtex 357 County Avenue Secaucus, NJ 07094 Key Test: CA TB 117-2013 (Section 1-Cover

Fabric) /ACT Tel: 1-(201)-917-7738

Ext:

Fax: 1-(201)-917-7764

Test Category: Cigarette Ignition

Product Category: Upholstery

Specifier: ACT

LE 2015; V 08/15

PC: 24H

dl/SM

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.) --

As cited by the ACT Voluntary Performance Guidelines (January 2015)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: SRM 1196 Cigarette

SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density 1.8  $\pm$  0.05 lb/ft $^3$ 

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure 8" x 8" x 2". The horizontal or seat cushions measure 8" x 5" x 2".

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received:05/03/2016 | Completed:05/04/2016 | Letter: V BG | **P.O.**#: Test Report #: 3-13142-0-Client's Product Name: Hem Stitch 3752. Fiber Content: 99% Recycled Polyester, 1% Polyester, 57" wide. 11.5 oz/lyd. No Finish. Identification No Back. Tested For: Teesha Prezeau Key Test: CA TB 117-2013 (Section 1-Cover 235 Designtex Fabric) /ACT 357 County Avenue **Tel:** 1-(201)-917-7738 Ext: Secaucus, NJ 07094 Fax: 1-(201)-917-7764

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
  - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ae1) of more than 1.8 inches (45 mm) develops on the cover fabric.
  - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E 1353 does recognize this phenomenon.

The Govmark report evaluates replacement cigarettes as follows:

If a cigarette self-extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing/Failure" conclusion.



Page 3

Received: 05/03/2016			BG <b>P.O.</b> #:		Test Report #:		3142-0-
Client's Produ Identification No Ba	ct Name: Hem Stite ack.	ch 3752. Fiber Content:	99% Recycled Pol	ester, 1% Polye	ster, 57" wide. 1	1.5 oz/lyd. No	Finish.
Tested For: Teesha Prezeau  Designtex 357 County Avenue			Key Test: CA TB 117-2013 (Section 1-Cover 23: Fabric) /ACT				
	s, NJ 07094			Tel: 1-(201) Fax: 1-(201)		Ext:	
RESULTS:						<u> </u>	THE STATE OF THE S
	Specimen #	Char Length (inches)	SE (yes/no)	SB45 (yes/no)	TOF (yes/no)		
Initial:	1	0.5	No	No	No		
	2	0.5	No	No	No		
	3	0.4	No	No	No		
Replacement:	1						
(If needed)	2						
	3						
Repeat Tests:	1						
(If needed)	1 2						
, ,	3						
EXPLANATION:							
Initial:	These are the draw a test co	first 3 cigarette	s where the re	sults could }	oe sufficient	to.	
Replacement:	If any of the initial cigarettes self-extinguish before burning their complete length, a new test is conducted with a fresh cigarette.						
Repeat Test:	Depending on the initial or replacement results, 3 repeat tests might be required to draw a conclusion.						
CODES USED:							
SB45 = Smolder TOF = Transit	beyond 45 min ions to open f	laming	-				
MNR = Measure	ment not recor	ded as smoldering	exceeded 45 mi	nutes or spe	ecimen		
EC = Escalat	<pre>ioned to open ing smoldering ):</pre>	flames combustion: Extir due to unsafe	nguished by tec conditions.	hnician at:			
CONCLUSION: The above resu indicate:	lts reported f	or the initial and	l / or replacem	ent cigarett	es are suffic	cient to	
[x] Passing	; [ ] Failure	; [ ] Repeat test	on 3 additiona	l specimens			
The results af	ter conducting	the repeat tests	indicate:				
[ ] Passing	; [ ] Failure						
		( P	age 3 of 4)				



Page 4

Received: 05/03/2016 Completed: 05/04/2016 Letter: V BG | P.O.#: Test Report #: 3-13142-0-Product Name: Hem Stitch 3752. Fiber Content: 99% Recycled Polyester, 1% Polyester, 57" wide. 11.5 oz/lyd. No Finish. Client's Identification No Back. Tested For: Teesha Prezeau Key Test: CA TB 117-2013 (Section 1-Cover Designtex Fabric) /ACT 357 County Avenue Tel: 1-(201)-917-7738 Ext: Secaucus, NJ 07094 Fax: 1-(201)-917-7764

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

GOVMARK

MAY 0 9 2016

/ec

Ms. Phyllis Pettit

(Page 4 of 4)