

**3869 Net was tested and met the following flammability requirements:**

CA TB 117-2013

### certificate of testing

client Designtex  
357 County Ave  
Secaucus, NJ 07094

product identification Net 3869

**test method performed** smolder resistance of materials used in upholstered furniture – section 1: cover fabrics  
california technical bulletin 117: 2013 (january 2019 revision)

**date of test** 3.13.2023

### test results

specimen	char length (in.)	extinguished <45 min (y/n)
1	0.5	y
2	0.5	y
3	0.5	y

### notes

test conditions 70 ±3.5°F, 50 ±5% relative humidity *requirement: 21 ±3°C, less than 55% relative humidity*  
sampling as received  
ignition source srm1196a  
deviations none

### acceptance criteria

- pass
- vertical char length ≤1.8 inches (45mm)
  - smoldering extinguishes within 45 minutes
  - no transition to open flaming
- fail
- vertical char >1.8 inches (45mm)
  - smoldering beyond 45 minutes
  - specimens transition to open flaming
- retest
- if only one of the three initial specimens fail, retest an additional three specimens
  - if all three additional specimens pass the test, the cover fabric passes the test
  - if any one of the additional three specimens fail, the cover fabric fails the test

### classification

based upon the test results and acceptance criteria listed above, the product identified is a

- pass  
 fail  
 requires retesting

**certification statement** by signing below, the lab certifies that the results were obtained after testing specimens submitted by the client in accordance to the procedures and equipment specified by the standard stated above.

approved by: 