Flammability Certificate 3888 Hyde

Designtex

3888 Hyde was tested and met the following flammability requirements:

CA TB 117-2013



Ext:

Page 1

235

 Received:09/22/2017
 Completed:09/26/2017
 Letter: D
 BG
 P.O.#: TS2007
 Test Report #:
 3-21352-0

Client's Identification

Item Number: 3888. Style: Hyde. Composition: 100% Vinyl.

Tested For: Hortensia Cowart-King

Key Test: CA TB 117-2013 (Section 1-Cover

Fabric)

Designtex 357 County Avenue

Tel: 1-(201)-917-7726

Secaucus, NJ 07094 Fax: 1-(201)-917-7764

NTR 04/16

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: SRM 1196 Cigarette

SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density 1.8 \pm 0.05 lb/ft 3

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure $8" \times 8" \times 2"$. The horizontal or seat cushions measure $8" \times 5" \times 2"$.

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received: 09/22	/2017 Completed: 09/26/2017	Letter: D	BG	P.O.#: TS2007	Test Report #:	3-2	21352-0-
Client's Identification	Item Number: 3888. Style: Hyd	de. Composition:	100%	Vinyl.			
Tested For: Hortensia Cowart-King				Key Test:	y Test: CA TB 117-2013 (Section 1-Cover		
De	esigntex				Fabric)		
35	7 County Avenue			Tel:	1-(201)-917-7726	Ext:	
Se	caucus, NJ 07094			Fax:	1-(201)-917-7764		

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
 - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ael) of more than 1.8 inches (45 mm) develops on the cover fabric.
 - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E 1353 does recognize this phenomenon.

The Govmark report evaluates replacement cigarettes as follows:

If a cigarette self extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing/Failure" conclusion.

(Page 2 of 4)



Page 3

Received:09/22/2017	Completed: 09/26/2	2017 Letter: D	BG P.O. #: T	S2007	Test Report #:	3-21	352-0-	
Client's Item N Identification	lumber: 3888. Style	: Hyde. Composition	: 100% Vinyl.					
Tested For: Hortens Designte	_				A TB 117-2013 (Sect	ion 1-Cover	235	
	nty Avenue s, NJ 07094				(201)-917-7726 (201)-917-7764	Ext:		
RESULTS:								
	Specimen #	Char Length (inches)	SE (yes/no)	SB45 (yes/no)	TOF (yes/no)			
Initial:	1 2	0	Yes Yes	No No	No No			
	3	0	Yes	No	No			
Replacement: (If needed)	1 2 3	0 0 0	Yes Yes Yes	No No No	No No No			
Repeat Tests: (If needed)	1 2 3		202					
EXPLANATION:								
Initial:	These are the first 3 cigarettes where the results could be sufficient to draw a test conclusion.							
Replacement:			rettes self-extinguish before burning their complete acted with a fresh cigarette.					
Repeat Test:	Repeat Test: Depending on the initial or replacement results, repeat tests might be required to draw a conclusion.							
SB45 = Smolde TOF = Transi MNR = Measure transi EC = Escala	r beyond 45 min tions to open f ement not recon tioned to open ting smoldering	flaming cded as smolderi	ng exceeded 4	15 minutes c				
CONCLUSION:								
The above resindicate:	ults reported i	for the initial	and / or repl	lacement cig	arettes are suff	ficient to		
[x] Passin	g; [] Failure	e; [] Repeat te	st on 3 addit	cional speci	mens			
The results a	fter conducting	g the repeat tes	ts indicate:					
[] Passin	g; [] Failure	(Pa	ge 3 of 4)					



Page 4

Received: 09/2	22/2017 Completed: 09/26/2017	Letter: D	BG	P.O.#: TS2007	Test Report #:	3	-21352-0-
Client's Identification	Item Number: 3888. Style: Hyd	e. Composition:	100%	Vinyl.			
Tested For: Hortensia Cowart-King Key Test: CA TB 117-2013 (Section 1-Cover						235	
]	Designtex				Fabric)		
357 County Avenue			Tel:	1-(201)-917-7726	Ext:		
	Secaucus, NJ 07094			Fax:	1-(201)-917-7764		

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED STANATURE GOVMARK

/pm/mo

(Page 4 of 4)

Douglas W. Lipp

SEP 2 7 2017