

3889 Metallo was tested and met the following flammability requirements:

CA TB 117-2013

DESIGNTex

357 County Ave
Secaucus, NJ 07094
201 866 9002 Phone
201 866 8856 Fax
800 221 1540 Samples. Orders. Information.
www.designtex.com

A Steelcase Company

Product Services Department
357 County Avenue
Secaucus, NJ 07094

To Whom It May Concern

The attached Applied Testing report 78160 referencing the developmental name Clarke was provided by the mill as representative of Designtex Metallo 3889. It meets the requirements for Cal 117-2013

Sincerely,

Adity Phadnis

Signature, title
Product Services

Please contact aphadnis@designtex.com for any questions.

CERTIFICATE OF TESTING

For the Account Of: Nassimi LLC
 370 Seventh Ave.
 Suite 1600
 New York, NY 10001

Contact: Cindy Barzola

Client's Identification: Clarke

TEST PERFORMED California Technical Bulletin 117: June 2013 – Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture – Cover Fabric Test

TEST RESULTS

Specimen	Char Length (in)	Extinguished in 45 minutes? (Y/N)
1	Self-Extinguished	Y
2	Self-Extinguished	Y
3	Self-Extinguished	Y

NOTES

Test Conditions: 70 ±5°F, 50 ±5% Relative Humidity

ACCEPTANCE CRITERIA

A material is considered to pass or fail based on the following criteria:

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a. The mock-up test specimen continues to smolder after the 45 minute test duration
 - b. A vertical char length of more than 1.8 inches (45mm) develops on the cover fabric
 - c. The mock-up test specimen transitions to open flaming
2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e. the cigarettes burn their full length and are no longer smoldering
3. If more than one initial specimen fails, the cover fabric fails the test
4. If any one of the three initial specimens fails, repeat the test on additional three specimens
5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test

CONCLUSION

Based on the above Results and Acceptance Criteria, the item tested is:

- ☒ Pass
☐ Fail

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Authorized Signature-ME

